

Direct Burial Duct



1. All duct is produced with integral solvent-weld bells. Plain-end duct may be available.
2. Duct is produced in 20-foot lengths.
3. Duct color is gray.
4. Weights based on 500,000 psi modulus compound. 400,000 psi modulus compound is available.

DB-60

Conforms to: NEMA TC 6 & 8, ASTM F 512

Item Number	Trade Size	Average Outside Diameter (inches)	Approximate Inside Diameter (inches)	Minimum Wall Thickness (inches)	Approximate Weight (lbs/100')
4802000603	2	2.375	2.24	0.060	35
4803000603	3	3.500	3.30	0.092	76
4804000603	4	4.500	4.24	0.121	130
4805000603	5	5.563	5.23	0.152	190
4806000603	6	6.625	6.23	0.182	270

DB-100

Conforms to: NEMA TC 6 & 8, ASTM F 512

Item Number	Trade Size	Average Outside Diameter (inches)	Approximate Inside Diameter (inches)	Minimum Wall Thickness (inches)	Approximate Weight (lbs/100')
4803001003	3	3.500	3.26	0.112	89
4804001003	4	4.500	4.18	0.145	150
4805001003	5	5.563	5.17	0.179	230
4806001003	6	6.625	6.16	0.213	320

DB-120

Conforms to: NEMA TC 6 & 8, ASTM F 512, PTS 66 (1", 1½" & 2")

Item Number	Trade Size	Average Outside Diameter (inches)	Approximate Inside Diameter (inches)	Minimum Wall Thickness (inches)	Approximate Weight (lbs/100')
4801001203	1	1.315	1.18	0.060	18
4801501203	1½	1.900	1.77	0.060	28
4802001203	2	2.375	2.21	0.077	43
4803001203	3	3.500	3.24	0.118	95
4804001203	4	4.500	4.17	0.154	160
4805001203	5	5.563	5.15	0.191	240
4806001203	6	6.625	6.13	0.277	340